

48 PAPERING WORK, FLOORING AND CARPETING

48.00 GENERAL

48.00.32 TRANSMISSION OF INFORMATION: MAINTENANCE INSTRUCTIONS

01. MAINTENANCE INSTRUCTIONS

Maintenance instructions provided by the contractor:

- PVC Veka leakproof tiles.

Number of copies to be provided: Singular on paper and as a PDF file submitted to the management.

Time of providing: at completion.

48.00.40 RISK ALLOCATION AND WARRANTY: GENERAL

01. PARTS TO ENSURE

For the following parts, a guarantee is required which should apply from the moment of completion or the delivery of the guaranteed part during the indicated period.

Part: leakproof floor system on a new and existing surface.

- Guaranteed by: the constructor/ subcontractor
- Period of time: 3 years (except joint sealing in and around the PVC flooring system; a one-year warranty applies here).

48.43 RESILIENT FLOORING

48.43.10-a RESILIENT FLOORING

0. RESILIENT FLOORING

Fixing method: fully bonded with a 2K PU adhesive.

Pattern: to be determined square grid

Seam finishes: double seam finish:

- Around with a lap joint which are secured together with seizure.
- Thermal seam finish by means of welding wire.

Baseboards are manufactured, various heights possible.

Decking around and linings to be sealed and/ or grouted. Sealants and casting compounds as indicated by provider Vekavloeren b.v.

Pasted elastic floor coverings should be over the entire surface adhering to the substrate.

1. PLASTIC FLOORING

Provider: Vekavloeren B.V.

Product: Leakproof Veka Original flooringsystem through lap joint floor tile.

Form: tiles flat on top surface

Composition: Produced from high-quality recycled PVC material.

Color: standard color to be determined.

Performance requirements:

- European classification (EN 685): class 34-43.
- Fire behavior (DIN EN 13501-1): Bfl-S1.
- Impression load (EN 433): 0,1 mm.
- Chemical resistance (EN 433): highly resistant (assessment index 0).
- Abrasion (EN 660-1): Abrasion Class P.
- Dimensional Stability (EN 434): <0,1%.
- Thickness (mm): 6.
- Weight: (EN 430 (kg/m²)): 8,3
- Size floor tile (length x width) (mm): 500 x 500

Attachments:

- Welding wire in color of choice from standard collection
- Polymerkit
- PU molding material in color

5. ADHESIVE

Type: as stated by Vekavloeren.

.01 CANTILEVERED FLOOR, INSIDE

Leakproof Veka tiles in the area according to the design.